

Research Article

River Network HyperGraphs and Transportation Network HyperGraphs: A Graph-Theoretic Approach for Geoscientific and Civil Applications

Takaaki Fujita^{1*}¹Independent Researcher, Shinjuku, Shinjuku-ku, Tokyo, Japan.*Corresponding author: Takaaki.fujita060@gmail.com

Article Info

Keywords: Superhypergraph, Hypergraph, River Network HyperGraph, Transportation Network HyperGraph.

Received: 12.07.2025

Accepted: 18.08.2025

Published: 25.08.2025



© 2025 by the author's. The terms and conditions of the Creative Commons Attribution (CC BY) license apply to this open access article.

Abstract

River Network Graphs and Transportation Network Graphs are classical models that represent river systems and transportation infrastructures as vertices and edges, respectively, and underpin applications in hydrological simulation, watershed management, shortest-path computation, and urban traffic analysis. In this paper, we extend these graph-based models into the hypergraph and superhypergraph domains by introducing two new structures—River Network HyperGraph and Transportation Network HyperGraph—and their hierarchical generalizations, River Network SuperHyperGraph and Transportation Network SuperHyperGraph. These enhanced representations enable multi-scale, hierarchical modeling of waterway and transportation networks, offering a unified framework for advanced analysis and management of complex infrastructure systems.

1. Introduction

We begin by fixing notation and recalling foundational definitions that will be used throughout this paper. Unless otherwise specified, all graphs are assumed to be finite. For more extensive treatments, see the referenced works.

1.1. Hypergraphs and SuperHyperGraphs

Graph theory is the mathematical study of networks of vertices and edges representing relationships or connections [1–3]. A *hypergraph* extends the notion of a graph by permitting each *hyperedge* to join any nonempty subset of vertices at once [4–7]. Hypergraphs have been applied in a wide range of domains, and various mathematical properties and graph algorithms have been developed to analyze them [8–11]. A *SuperHyperGraph* further builds a hierarchy by iterating the powerset construction, thus capturing nested, multi-scale relationships among vertices and edges [12–18].

Definition 1.1 (Base set). *Let V_0 be a finite set, called the base set. All subsequent vertex and edge collections are drawn from V_0 or its iterated powersets.*

Definition 1.2 (Powerset). *For any set X , its powerset is*

$$\mathcal{P}(X) = \{A : A \subseteq X\}.$$

Definition 1.3 (Hypergraph). [4, 6] A hypergraph is a pair $H = (V, E)$ where

- V is a finite set of vertices, and
- $E \subseteq \mathcal{P}(V) \setminus \{\emptyset\}$ is a finite collection of nonempty subsets of V , called hyperedges.

Example 1.4 (Urban Bus Network Hypergraph). Consider a small downtown bus system with four major stops:

$$V = \{\text{Central, Museum, CityHall, Airport}\}.$$

The bus routes serve these stops as follows:

$$e_1 = \{\text{Central, Museum, CityHall}\},$$

$$e_2 = \{\text{Central, CityHall, Airport}\},$$

$$e_3 = \{\text{Museum, CityHall, Airport}\}.$$

Then the hypergraph

$$H = (V, E), \quad E = \{e_1, e_2, e_3\},$$

models the overlapping coverage of the three bus routes in the urban core.

Definition 1.5 (Iterated powerset). [19–21] Define recursively for $k \geq 0$:

$$\mathcal{P}^0(V_0) = V_0, \quad \mathcal{P}^{k+1}(V_0) = \mathcal{P}(\mathcal{P}^k(V_0)).$$

We write $\mathcal{P}_n(V_0)$ for $\mathcal{P}^n(V_0)$ and denote by $\mathcal{P}_n^*(V_0)$ its collection of nonempty subsets.

Example 1.6 (Iterated powerset for the Tokaido Shinkansen). Let the base set of key stations on the Tokaido Shinkansen be

$$V_0 = \{\text{Tokyo, Nagoya, Kyoto, Shin-Osaka}\}.$$

Then the first iterated powerset

$$\mathcal{P}^1(V_0) = \mathcal{P}(V_0)$$

is the collection of all nonempty station subsets, for example

$$\{\text{Tokyo}\}, \quad \{\text{Nagoya, Kyoto}\}, \quad \{\text{Tokyo, Shin-Osaka}\}, \quad \dots$$

Here, $\{\text{Nagoya, Kyoto}\}$ might represent a service stopping only at Nagoya and Kyoto.

Next, the second iterated powerset

$$\mathcal{P}^2(V_0) = \mathcal{P}(\mathcal{P}(V_0))$$

consists of all nonempty collections of these station-sets. For instance,

$$\{\{\text{Tokyo, Nagoya}\}, \{\text{Kyoto, Shin-Osaka}\}\} \in \mathcal{P}^2(V_0),$$

which can be interpreted as grouping two distinct service patterns: one linking Tokyo–Nagoya and another linking Kyoto–Shin-Osaka.

Definition 1.7 (n -SuperHyperGraph). [22, 23] An n -SuperHyperGraph is a pair

$$\text{SuHyG}^{(n)} = (V, E), \quad V, E \subseteq \mathcal{P}^n(V_0),$$

where each element of V is called an n -supervertex and each element of E an n -superedge.

Example 1.8 (River Network 2-SuperHyperGraph of the Amazon Basin). Let the base set of river confluences be

$$V_0 = \{\text{RioNegro, Madeira, Solimões, Amazonas}\}.$$

In the underlying River Network HyperGraph, we have the hyperedges

$$e_{RNA} = \{\text{RioNegro, Amazonas}\},$$

$$e_{MAA} = \{\text{Madeira, Amazonas}\},$$

$$e_{SAA} = \{\text{Solimões, Amazonas}\},$$

$$e_{\text{Main}} = \{\text{RioNegro, Madeira, Solimões, Amazonas}\}.$$

Typical mean annual discharges (in m^3/s) and channel lengths (in km) are

$$\varphi(e_{RNA}) = 2.83 \times 10^4, \quad \ell(e_{RNA}) = 2430,$$

$$\varphi(e_{MAA}) = 3.15 \times 10^4, \quad \ell(e_{MAA}) = 3200,$$

$$\varphi(e_{SAA}) = 1.60 \times 10^4, \quad \ell(e_{SAA}) = 1600,$$

$$\varphi(e_{\text{Main}}) = 2.83 \times 10^4 + 3.15 \times 10^4 + 1.60 \times 10^4 = 7.58 \times 10^4, \quad \ell(e_{\text{Main}}) = \max\{2430, 3200, 1600\} = 3200.$$

For $n = 2$, the 2-SuperHyperGraph is

$$V_2 = \mathcal{P}^2(V_0), \quad E_2 = \{ \mathcal{P}(e) \setminus \{\emptyset\} \mid e \in \{e_{RNA}, e_{MAA}, e_{SAA}, e_{\text{Main}}\} \},$$

with propagated labelings

$$\varphi^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \varphi(e), \quad \ell^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \ell(e).$$

Two representative superedges are:

• **Tributary superedge at Rio Negro:**

$$\mathcal{P}(e_{RNA}) \setminus \{\emptyset\} = \{\{\text{RioNegro}\}, \{\text{Amazonas}\}, \{\text{RioNegro}, \text{Amazonas}\}\},$$

carrying $\varphi^{(2)} = 2.83 \times 10^4 \text{ m}^3/\text{s}$ and $\ell^{(2)} = 2430 \text{ km}$.

• **Main-stem superedge of the basin:**

$$\mathcal{P}(e_{\text{Main}}) \setminus \{\emptyset\} = \{\{\text{RioNegro}\}, \{\text{Madeira}\}, \{\text{Solimões}\}, \{\text{Amazonas}\}, \dots,$$

$$\{\text{RioNegro}, \text{Madeira}, \text{Solimões}, \text{Amazonas}\}\},$$

carrying $\varphi^{(2)} = 7.58 \times 10^4 \text{ m}^3/\text{s}$ and $\ell^{(2)} = 3200 \text{ km}$.

Example 1.9 (Urban Road Network 2-SuperHyperGraph of the Times–Herald–Union Triangle). *We model three major intersections in Midtown Manhattan as the Transportation Network Graph*

$$G = (V, E, \tau, \ell, \kappa),$$

with

$$V = \{\text{TimesSq}, \text{HeraldSq}, \text{UnionSq}\},$$

$$E = \{(\text{TimesSq}, \text{HeraldSq}), (\text{HeraldSq}, \text{UnionSq}), (\text{TimesSq}, \text{UnionSq})\},$$

where each road is bidirectional. Typical parameters on each undirected link are:

$$\tau(\text{TimesSq}, \text{HeraldSq}) = 2 \text{ min}, \quad \ell(\text{TimesSq}, \text{HeraldSq}) = 0.4 \text{ km}, \quad \kappa(\text{TimesSq}, \text{HeraldSq}) = 1000 \text{ veh/h},$$

$$\tau(\text{HeraldSq}, \text{UnionSq}) = 3 \text{ min}, \quad \ell(\text{HeraldSq}, \text{UnionSq}) = 0.6 \text{ km}, \quad \kappa(\text{HeraldSq}, \text{UnionSq}) = 800 \text{ veh/h},$$

$$\tau(\text{TimesSq}, \text{UnionSq}) = 5 \text{ min}, \quad \ell(\text{TimesSq}, \text{UnionSq}) = 0.9 \text{ km}, \quad \kappa(\text{TimesSq}, \text{UnionSq}) = 1200 \text{ veh/h}.$$

Its Transportation Network HyperGraph has hyperedges

$$\mathcal{E} = \{\{\text{TimesSq}, \text{HeraldSq}\}, \{\text{HeraldSq}, \text{UnionSq}\}, \{\text{TimesSq}, \text{UnionSq}\}, \{\text{TimesSq}, \text{HeraldSq}, \text{UnionSq}\}\},$$

where the last set is the junction hyperedge at Herald Square (all three roads meet).

For $n = 2$, the 2-SuperHyperGraph is

$$V_2 = \mathcal{P}^2(V), \quad E_2 = \{\mathcal{P}(e) \setminus \{\emptyset\} \mid e \in \mathcal{E}\},$$

with weight-functions inherited from level 1:

$$\tau^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \tau_H(e), \quad \ell^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \ell_H(e), \quad \kappa^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \kappa_H(e).$$

Two illustrative level-2 superedges are:

(a) **Binary connection at Times–Herald:**

$$\mathcal{P}(\{\text{TimesSq}, \text{HeraldSq}\}) \setminus \{\emptyset\} = \{\{\text{TimesSq}\}, \{\text{HeraldSq}\}, \{\text{TimesSq}, \text{HeraldSq}\}\},$$

carrying $\tau^{(2)} = 2 \text{ min}$, $\ell^{(2)} = 0.4 \text{ km}$, $\kappa^{(2)} = 1000 \text{ veh/h}$.

(b) **Junction at HeraldSq:**

$$\begin{aligned} \mathcal{P}(\{\text{TimesSq}, \text{HeraldSq}, \text{UnionSq}\}) \setminus \{\emptyset\} = & \{\{\text{TimesSq}\}, \{\text{HeraldSq}\}, \{\text{UnionSq}\}, \\ & \{\text{TimesSq}, \text{HeraldSq}\}, \{\text{TimesSq}, \text{UnionSq}\}, \{\text{HeraldSq}, \text{UnionSq}\}, \\ & \{\text{TimesSq}, \text{HeraldSq}, \text{UnionSq}\}\}, \end{aligned}$$

with $\tau^{(2)} = \max\{2, 3, 5\} = 5 \text{ min}$, $\ell^{(2)} = \max\{0.4, 0.6, 0.9\} = 0.9 \text{ km}$, $\kappa^{(2)} = 1000 + 800 + 1200 = 3000 \text{ veh/h}$.

2. River Network Graph and Their Extensions

River networks are interconnected branching systems of channels and streams that transport water and sediments across drainage basin landscapes continuously (cf.[24–27]). A River Network Graph is a graph that represents rivers and their tributary connections as vertices and edges, used in flow simulations and watershed management (cf.[28–30]). We extend this concept using hypergraphs and superhypergraphs.

Definition 2.1 (River Network Graph). *A River Network Graph is a directed acyclic graph*

$$G = (V, E, \varphi, \ell),$$

equipped with

- a finite set of nodes V , whose elements are
 - sources (head-water confluences or springs),
 - junctions (confluence of two or more upstream channels), and

- sinks (river mouth or gauging station).
- a set of directed edges $E \subseteq V \times V$, where $(u, v) \in E$ if and only if there is a river channel carrying flow from node u downstream to node v . The requirement that G is acyclic (no directed cycles) encodes the fact that water cannot flow uphill back into an upstream channel.
- a function $\varphi : E \rightarrow \mathbb{R}_{>0}$ assigning each edge $e = (u, v)$ a stream discharge capacity $\varphi(e)$ (e.g. mean annual flow).
- a function $\ell : E \rightarrow \mathbb{R}_{>0}$ assigning each edge e its channel length $\ell(e)$.

We may represent G by its adjacency matrix $A \in \{0, 1\}^{|V| \times |V|}$ with

$$A_{uv} = \begin{cases} 1, & (u, v) \in E, \\ 0, & \text{otherwise,} \end{cases}$$

and by weighted matrices $\Phi, \Lambda \in \mathbb{R}^{|V| \times |V|}$ with $\Phi_{uv} = \varphi(u, v)$ and $\Lambda_{uv} = \ell(u, v)$.

Example 2.2 (River Network Graph of the Mississippi–Ohio System). Consider the major confluences in the Mississippi–Ohio watershed (cf. [31–33]). We model this as the directed acyclic graph

$$G = (V, E, \varphi, \ell),$$

where

$$\begin{aligned} V = & \{ \text{Allegheny Source (Lake Pleasant, NY),} \\ & \text{Monongahela Source (Fairmont, WV),} \\ & \text{Mississippi Source (Lake Itasca, MN),} \\ & \text{Pittsburgh (Allegheny + Monongahela),} \\ & \text{Cairo (Ohio + Mississippi),} \\ & \text{Gulf Mouth (Gulf of Mexico)} \}, \\ E = & \{ (\text{Allegheny Source, Pittsburgh}), (\text{Monongahela Source, Pittsburgh}), \\ & (\text{Pittsburgh, Cairo}), (\text{Mississippi Source, Cairo}), (\text{Cairo, Gulf Mouth}) \}. \end{aligned}$$

Stream discharge capacities (mean annual flow, in m^3/s) and channel lengths (in km) are recorded by

$$\begin{aligned} \varphi(e) = & \begin{cases} 560, & e = (\text{Allegheny Source, Pittsburgh}), \\ 340, & e = (\text{Monongahela Source, Pittsburgh}), \\ 7970, & e = (\text{Pittsburgh, Cairo}), \\ 16790, & e = (\text{Mississippi Source, Cairo}), \\ 17100, & e = (\text{Cairo, Gulf Mouth}), \end{cases} \\ \ell(e) = & \begin{cases} 981, & e = (\text{Allegheny Source, Pittsburgh}), \\ 499, & e = (\text{Monongahela Source, Pittsburgh}), \\ 1579, & e = (\text{Pittsburgh, Cairo}), \\ 3766, & e = (\text{Mississippi Source, Cairo}), \\ 1045, & e = (\text{Cairo, Gulf Mouth}). \end{cases} \end{aligned}$$

Definition 2.3 (River Network HyperGraph). Let $G = (V, E, \varphi, \ell)$ be a River Network Graph. We define its River Network HyperGraph

$$H = (V, \mathcal{E}, \varphi_H, \ell_H)$$

as follows:

- The vertex set of H is the same as that of G : $V(H) = V$.
- The hyperedge set $\mathcal{E}$ consists of two types of nonempty subsets of V :
 1. For each directed channel $(u, v) \in E$ in G , include the binary hyperedge

$$e_{u,v} = \{u, v\}.$$
 2. For each junction node $j \in V$ with at least two immediate upstream neighbors,

$$U_j = \{u \in V : (u, j) \in E\}, \quad |U_j| \geq 2,$$
 include the junction hyperedge

$$e_j = U_j \cup \{j\}.$$

- The capacity-labeling $\varphi_H : \mathcal{E} \rightarrow \mathbb{R}_{>0}$ is given by

$$\varphi_H(e) = \begin{cases} \varphi(u, v), & e = \{u, v\}, \\ \sum_{u \in U_j} \varphi(u, j), & e = e_j, \end{cases}$$

i.e. binary edges inherit the channel capacity, and junction hyperedges aggregate upstream capacities.

- The length-labeling $\ell_H : \mathcal{E} \rightarrow \mathbb{R}_{>0}$ is given by

$$\ell_H(e) = \begin{cases} \ell(u, v), & e = \{u, v\}, \\ \max_{u \in U_j} \ell(u, j), & e = e_j, \end{cases}$$

i.e. junction hyperedges carry the maximum upstream reach length.

Example 2.4 (River Network HyperGraph of the Mississippi–Ohio System). We model the key confluences in the Mississippi–Ohio watershed as the hypergraph

$$H = (V, \mathcal{E}, \Phi_H, \ell_H),$$

where

$$V = \{ \text{Allegheny Source, Monongahela Source, Mississippi Source, Pittsburgh, Cairo, Gulf Mouth} \},$$

$$\mathcal{E} = \{ \{ \text{Allegheny Source, Pittsburgh} \}, \{ \text{Monongahela Source, Pittsburgh} \}, \{ \text{Pittsburgh, Cairo} \}, \{ \text{Mississippi Source, Cairo} \}, \{ \text{Allegheny Source, Monongahela Source, Pittsburgh} \}, \{ \text{Pittsburgh, Mississippi Source, Cairo} \} \}.$$

The capacity-labeling $\Phi_H : \mathcal{E} \rightarrow \mathbb{R}_{>0}$ is

$$\Phi_H(e) = \begin{cases} 560, & e = \{ \text{Allegheny Source, Pittsburgh} \}, \\ 340, & e = \{ \text{Monongahela Source, Pittsburgh} \}, \\ 7970, & e = \{ \text{Pittsburgh, Cairo} \}, \\ 16790, & e = \{ \text{Mississippi Source, Cairo} \}, \\ 560 + 340, & e = \{ \text{Allegheny Source, Monongahela Source, Pittsburgh} \}, \\ 7970 + 16790, & e = \{ \text{Pittsburgh, Mississippi Source, Cairo} \}. \end{cases}$$

The length-labeling $\ell_H : \mathcal{E} \rightarrow \mathbb{R}_{>0}$ is

$$\ell_H(e) = \begin{cases} 981, & e = \{ \text{Allegheny Source, Pittsburgh} \}, \\ 499, & e = \{ \text{Monongahela Source, Pittsburgh} \}, \\ 1579, & e = \{ \text{Pittsburgh, Cairo} \}, \\ 3766, & e = \{ \text{Mississippi Source, Cairo} \}, \\ \max\{981, 499\}, & e = \{ \text{Allegheny Source, Monongahela Source, Pittsburgh} \}, \\ \max\{1579, 3766\}, & e = \{ \text{Pittsburgh, Mississippi Source, Cairo} \}. \end{cases}$$

Theorem 2.5. For any River Network Graph $G = (V, E, \phi, \ell)$, the structure H of the Definition is a hypergraph that generalizes G :

1. H satisfies the hypergraph axioms (each hyperedge is a nonempty subset of V).
2. The 2-section (or clique-expansion) of H recovers the undirected version of G : every $(u, v) \in E$ appears as an edge in the graph whose edges are all unordered pairs contained in some $e \in \mathcal{E}$.

Proof. We verify each claim in turn.

(1) Hypergraph axioms. By construction, each binary hyperedge $e_{u,v} = \{u, v\}$ is nonempty since $(u, v) \in E$ implies $u \neq v$. Each junction hyperedge

$$e_j = U_j \cup \{j\}$$

is nonempty because $|U_j| \geq 2$ by hypothesis, and $j \notin U_j$ by acyclicity of G . Hence $\mathcal{E} \subseteq \mathcal{P}(V) \setminus \{\emptyset\}$, so H is a hypergraph.

(2) Generalization via 2-section. Define the 2-section (or clique-expansion) graph $\Gamma(H) = (V, E')$ by

$$E' = \{ \{x, y\} \subseteq V \mid \exists e \in \mathcal{E}, \{x, y\} \subseteq e \}.$$

- Every original channel $(u, v) \in E$ yields the binary hyperedge $e_{u,v}$, so $\{u, v\} \subseteq e_{u,v}$. Hence $\{u, v\} \in E'$.
- Conversely, if $\{u, v\} \in E'$, then there exists some hyperedge e with $\{u, v\} \subseteq e$. If $e = e_{x,y}$ is binary, then $(x, y) \in E$ and $\{u, v\} = \{x, y\}$. If $e = e_j$ is a junction hyperedge, then $u, v \in U_j \cup \{j\}$. In this case at least one of $\{u, v\}$ is of the form $\{u', j\}$ with $(u', j) \in E$, so the directed edge $(u', j) \in E$ implies $\{u', j\} \in E'$. Thus every pair in E' corresponds to some original channel in E .

Therefore $\Gamma(H)$ is exactly the (undirected) edge-set of G . This shows that H indeed generalizes G via clique-expansion. $\square$

Definition 2.6 (River Network n -SuperHyperGraph). Let $G = (V, E, \varphi, \ell)$ be a River Network Graph and let

$$\mathcal{E} = \{e \subseteq V : e \text{ is a hyperedge of the River Network HyperGraph of } G\}$$

be its hyperedge family. For any integer $n \geq 1$, the River Network n -SuperHyperGraph is

$$\text{RNHG}^{(n)} = (V_n, E_n, \varphi^{(n)}, \ell^{(n)}),$$

where for each $k = 1, \dots, n$:

$$V_k = \mathcal{P}^k(V), \quad E_k = \{\mathcal{P}^{k-1}(e) \mid e \in \mathcal{E}\} \subseteq \mathcal{P}(V_k) \setminus \{\emptyset\},$$

and the capacity- and length-labelings are propagated by

$$\varphi^{(k)}(\mathcal{P}^{k-1}(e)) = \varphi(e), \quad \ell^{(k)}(\mathcal{P}^{k-1}(e)) = \ell(e).$$

Example 2.7 (River Network 2-SuperHyperGraph of the Mississippi–Ohio System). Let $G = (V, E, \varphi, \ell)$ and $\mathcal{E}$ be as in Example 3.2. For $n = 2$, the River Network 2-SuperHyperGraph is

$$V_2 = \mathcal{P}^2(V), \quad E_2 = \{\mathcal{P}(e) \setminus \{\emptyset\} \mid e \in \mathcal{E}\},$$

with labelings

$$\varphi^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \varphi(e), \quad \ell^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \ell(e).$$

We illustrate two representative superedges:

(a) Binary channel at Pittsburgh:

For the channel hyperedge

$$e_{AP} = \{\text{Allegheny Source}, \text{Pittsburgh}\},$$

its level-2 superedge is

$$\mathcal{P}(e_{AP}) \setminus \{\emptyset\} = \{\{\text{Allegheny Source}\}, \{\text{Pittsburgh}\}, \{\text{Allegheny Source}, \text{Pittsburgh}\}\}.$$

This inherits capacity and length

$$\varphi^{(2)}(\mathcal{P}(e_{AP}) \setminus \{\emptyset\}) = \varphi(e_{AP}) = 560, \quad \ell^{(2)}(\mathcal{P}(e_{AP}) \setminus \{\emptyset\}) = \ell(e_{AP}) = 981.$$

(b) Junction at Pittsburgh:

For the junction hyperedge

$$e_P = \{\text{Allegheny Source}, \text{Monongahela Source}, \text{Pittsburgh}\},$$

its level-2 superedge is

$$\begin{aligned} \mathcal{P}(e_P) \setminus \{\emptyset\} = & \{\{\text{Allegheny Source}\}, \{\text{Monongahela Source}\}, \{\text{Pittsburgh}\}, \\ & \{\text{Allegheny Source}, \text{Monongahela Source}\}, \{\text{Allegheny Source}, \text{Pittsburgh}\}, \\ & \{\text{Monongahela Source}, \text{Pittsburgh}\}, \{\text{Allegheny Source}, \text{Monongahela Source}, \text{Pittsburgh}\}\}. \end{aligned}$$

This superedge carries

$$\varphi^{(2)}(\mathcal{P}(e_P) \setminus \{\emptyset\}) = \varphi(e_P) = 560 + 340 = 900, \quad \ell^{(2)}(\mathcal{P}(e_P) \setminus \{\emptyset\}) = \max\{981, 499\} = 981.$$

Theorem 2.8. For each $n \geq 1$, $\text{RNHG}^{(n)}$ is an n -SuperHyperGraph and generalizes the River Network HyperGraph in the sense that

$$\text{RNHG}^{(1)} = (V_1, E_1, \varphi^{(1)}, \ell^{(1)}) \cong (V, \mathcal{E}, \varphi, \ell).$$

Proof. We verify both claims:

(i) n -SuperHyperGraph structure. By construction,

$$V_n = \mathcal{P}^n(V) \quad \text{and} \quad E_n \subseteq \mathcal{P}(V_n) \setminus \{\emptyset\},$$

so $\text{RNHG}^{(n)}$ exactly matches the definition of an n -SuperHyperGraph.

(ii) Generalization of the HyperGraph. When $n = 1$, note that $\mathcal{P}^0(e) = e$ for each hyperedge $e \in \mathcal{E}$. Hence

$$V_1 = \mathcal{P}^1(V) = \mathcal{P}(V), \quad E_1 = \{\mathcal{P}^0(e) \mid e \in \mathcal{E}\} = \mathcal{E},$$

and the labelings satisfy $\varphi^{(1)}(e) = \varphi(e)$, $\ell^{(1)}(e) = \ell(e)$. Thus $\text{RNHG}^{(1)} = (V_1, E_1, \varphi^{(1)}, \ell^{(1)})$ coincides exactly with the River Network HyperGraph $(V, \mathcal{E}, \varphi, \ell)$. This shows that for arbitrary $n \geq 1$, the construction extends and indeed generalizes the level-1 hypergraph to a fully hierarchical, n -layer superhypergraph. $\square$

3. Transportation Network Graph and Their Extensions

Transportation networks represent intersections (nodes) and road or rail links (edges) to optimize travel connectivity (cf.[34–37]). A Transportation Network Graph is a graph in which vertices represent intersections and edges represent road segments, widely applied in shortest-path computation, traffic congestion analysis, and urban planning (cf.[38–40]). We extend this concept using hypergraphs and superhypergraphs.

Definition 3.1 (Transportation Network Graph). A Transportation Network Graph is a weighted directed graph

$$G = (V, E, \tau, \ell, \kappa),$$

equipped with

- a finite set of nodes V , each representing a junction, intersection, station, or terminal;
- a set of directed edges $E \subseteq V \times V$, where $(u, v) \in E$ if and only if there is a viable transportation link (road segment, rail line, airway corridor, etc.) carrying traffic from node u to node v ;
- a travel-time function $\tau: E \rightarrow \mathbb{R}_{>0}$, assigning each edge $e = (u, v)$ its typical traversal time $\tau(e)$;
- a length (distance) function $\ell: E \rightarrow \mathbb{R}_{>0}$, assigning each edge e its physical length $\ell(e)$;
- a capacity function $\kappa: E \rightarrow \mathbb{R}_{>0}$, assigning each edge e its maximum flow capacity $\kappa(e)$ (e.g. vehicles per hour).

We may represent G by its adjacency matrix $A \in \{0, 1\}^{|V| \times |V|}$ with

$$A_{uv} = \begin{cases} 1, & (u, v) \in E, \\ 0, & \text{otherwise,} \end{cases}$$

and by weighted matrices $\tau, \ell, \kappa \in \mathbb{R}^{|V| \times |V|}$ with

$$\tau_{uv} = \begin{cases} \tau(u, v), & (u, v) \in E, \\ 0, & \text{otherwise,} \end{cases} \quad \ell_{uv} = \begin{cases} \ell(u, v), & (u, v) \in E, \\ 0, & \text{otherwise,} \end{cases} \quad \kappa_{uv} = \begin{cases} \kappa(u, v), & (u, v) \in E, \\ 0, & \text{otherwise.} \end{cases}$$

Example 3.2 (Transportation Network Graph of the I-90 Corridor). We model the segment of Interstate 90 (I-90) in the northeastern United States (cf.[41, 42]), connecting Boston, Worcester, Springfield, and Albany, as the directed graph

$$G = (V, E, \tau, \ell, \kappa),$$

where

$$V = \{\text{Boston, Worcester, Springfield, Albany}\},$$

$$E = \{(\text{Boston, Worcester}), (\text{Worcester, Boston}), (\text{Worcester, Springfield}), (\text{Springfield, Worcester}), (\text{Springfield, Albany}), (\text{Albany, Springfield})\}.$$

Typical travel times (in hours), distances (in kilometers), and capacities (vehicles per hour) are specified by

$$\tau(e) = \begin{cases} 1.25, & e = (\text{Boston, Worcester}), \\ 1.25, & e = (\text{Worcester, Boston}), \\ 1.00, & e = (\text{Worcester, Springfield}), \\ 1.00, & e = (\text{Springfield, Worcester}), \\ 1.50, & e = (\text{Springfield, Albany}), \\ 1.50, & e = (\text{Albany, Springfield}), \end{cases} \quad \ell(e) = \begin{cases} 113, & e = (\text{Boston, Worcester}), \\ 113, & e = (\text{Worcester, Boston}), \\ 88, & e = (\text{Worcester, Springfield}), \\ 88, & e = (\text{Springfield, Worcester}), \\ 137, & e = (\text{Springfield, Albany}), \\ 137, & e = (\text{Albany, Springfield}), \end{cases}$$

$$\kappa(e) = \begin{cases} 2000, & e = (\text{Boston, Worcester}), \\ 2000, & e = (\text{Worcester, Boston}), \\ 1800, & e = (\text{Worcester, Springfield}), \\ 1800, & e = (\text{Springfield, Worcester}), \\ 1500, & e = (\text{Springfield, Albany}), \\ 1500, & e = (\text{Albany, Springfield}). \end{cases}$$

Definition 3.3 (Transportation Network HyperGraph). Let $G = (V, E, \tau, \ell, \kappa)$ be a Transportation Network Graph. Its Transportation Network HyperGraph is

$$H = (V, \mathcal{E}, \tau_H, \ell_H, \kappa_H),$$

where

$$\begin{aligned} \mathcal{E} &= \{ \{u, v\} : (u, v) \in E \} \cup \\ &\{ \{i\} \cup \{j : (i, j) \in E\} : |\{j : (i, j) \in E\}| \geq 2 \} \cup \\ &\{ \{i\} \cup \{j : (j, i) \in E\} : |\{j : (j, i) \in E\}| \geq 2 \}. \end{aligned}$$

Each hyperedge $e \in \mathcal{E}$ is assigned

$$\begin{aligned}\tau_H(e) &= \begin{cases} \tau(u, v), & e = \{u, v\}, \\ \max_{(i,j) \in E, j \in e} \tau(i, j), & e = \{i\} \cup \{j : (i, j) \in E, |\cdot| \geq 2\}, \\ \max_{(j,i) \in E, j \in e} \tau(j, i), & e = \{i\} \cup \{j : (j, i) \in E, |\cdot| \geq 2\}, \end{cases} \\ \ell_H(e) &= \begin{cases} \ell(u, v), & e = \{u, v\}, \\ \max_{(i,j) \in E, j \in e} \ell(i, j), & e = \{i\} \cup \{j : (i, j) \in E, |\cdot| \geq 2\}, \\ \max_{(j,i) \in E, j \in e} \ell(j, i), & e = \{i\} \cup \{j : (j, i) \in E, |\cdot| \geq 2\}, \end{cases} \\ \kappa_H(e) &= \begin{cases} \kappa(u, v), & e = \{u, v\}, \\ \sum_{(i,j) \in E, j \in e} \kappa(i, j), & e = \{i\} \cup \{j : (i, j) \in E, |\cdot| \geq 2\}, \\ \sum_{(j,i) \in E, j \in e} \kappa(j, i), & e = \{i\} \cup \{j : (j, i) \in E, |\cdot| \geq 2\}. \end{cases}\end{aligned}$$

Example 3.4 (Transportation Network HyperGraph of the I-90 Corridor). Let $G = (V, E, \tau, \ell, \kappa)$ be the I-90 segment graph from Example 4.2. The corresponding Transportation Network HyperGraph

$$H = (V, \mathcal{E}, \tau_H, \ell_H, \kappa_H)$$

is given by

$$\begin{aligned}V &= \{\text{Boston, Worcester, Springfield, Albany}\}, \\ \mathcal{E} &= \{\{\text{Boston, Worcester}\}, \{\text{Worcester, Springfield}\}, \{\text{Springfield, Albany}\}, \\ &\quad \{\text{Worcester, Boston, Springfield}\}, \{\text{Springfield, Worcester, Albany}\}\}.\end{aligned}$$

The first three are binary hyperedges corresponding to directed links in E , and the last two are junction hyperedges at nodes with two outgoing roads.

The travel-time labeling τ_H is

$$\tau_H(e) = \begin{cases} 1.25, & e = \{\text{Boston, Worcester}\}, \\ 1.00, & e = \{\text{Worcester, Springfield}\}, \\ 1.50, & e = \{\text{Springfield, Albany}\}, \\ \max\{1.25, 1.00\} = 1.25, & e = \{\text{Worcester, Boston, Springfield}\}, \\ \max\{1.00, 1.50\} = 1.50, & e = \{\text{Springfield, Worcester, Albany}\}. \end{cases}$$

The distance labeling ℓ_H is

$$\ell_H(e) = \begin{cases} 113, & e = \{\text{Boston, Worcester}\}, \\ 88, & e = \{\text{Worcester, Springfield}\}, \\ 137, & e = \{\text{Springfield, Albany}\}, \\ \max\{113, 88\} = 113, & e = \{\text{Worcester, Boston, Springfield}\}, \\ \max\{88, 137\} = 137, & e = \{\text{Springfield, Worcester, Albany}\}. \end{cases}$$

The capacity labeling κ_H is

$$\kappa_H(e) = \begin{cases} 2000, & e = \{\text{Boston, Worcester}\}, \\ 1800, & e = \{\text{Worcester, Springfield}\}, \\ 1500, & e = \{\text{Springfield, Albany}\}, \\ 2000 + 1800 = 3800, & e = \{\text{Worcester, Boston, Springfield}\}, \\ 1800 + 1500 = 3300, & e = \{\text{Springfield, Worcester, Albany}\}. \end{cases}$$

Theorem 3.5. The structure $H = (V, \mathcal{E}, \tau_H, \ell_H, \kappa_H)$ of Definition 3.3 is a hypergraph that generalizes the Transportation Network Graph G in the sense that its 2-section recovers the undirected version of G .

Proof. First, each $e \in \mathcal{E}$ is by construction a nonempty subset of V , so H is a hypergraph.

Next, form the 2-section (clique-expansion) graph $\Gamma(H) = (V, E')$ with

$$E' = \{\{x, y\} \subseteq V : \exists e \in \mathcal{E}, \{x, y\} \subseteq e\}.$$

— If $(u, v) \in E$, then $\{u, v\} \in \mathcal{E}$, so $\{u, v\} \in E'$.

— Conversely, if $\{u, v\} \in E'$, then some $e \in \mathcal{E}$ contains $\{u, v\}$. If $e = \{u, v\}$ arises from a graph edge, we recover $(u, v) \in E$ (or (v, u)). If e is a junction hyperedge at node i , then $\{u, v\} \subseteq \{i\} \cup N(i)$, so at least one of $\{u, v\}$ corresponds to an original directed link into or out of i . Hence every pair in E' arises from some $(x, y) \in E$.

Therefore $\Gamma(H)$ coincides with the underlying undirected graph of G , proving that H indeed generalizes G . $\square$

Definition 3.6 (Transportation Network n -SuperHyperGraph). Let $G = (V, E, \tau, \ell, \kappa)$ be a Transportation Network Graph and let

$$\mathcal{E} = \{e \subseteq V : e \text{ is a hyperedge of the Transportation Network HyperGraph of } G\}.$$

For any integer $n \geq 1$, the Transportation Network n -SuperHyperGraph is the tuple

$$\text{TNHG}^{(n)} = (V_n, E_n, \tau^{(n)}, \ell^{(n)}, \kappa^{(n)}),$$

where:

$$V_n = \mathcal{P}^n(V), \quad E_n = \left\{ \mathcal{P}^{n-1}(e) \mid e \in \mathcal{E} \right\} \subseteq \mathcal{P}(V_n) \setminus \{\emptyset\},$$

and the weight-functions on each hyperedge $\mathcal{P}^{n-1}(e) \in E_n$ are propagated from the level-1 HyperGraph by

$$\tau^{(n)}(\mathcal{P}^{n-1}(e)) = \tau_H(e), \quad \ell^{(n)}(\mathcal{P}^{n-1}(e)) = \ell_H(e), \quad \kappa^{(n)}(\mathcal{P}^{n-1}(e)) = \kappa_H(e),$$

where $(\tau_H, \ell_H, \kappa_H)$ are the weight-functions of the Transportation Network HyperGraph.

Example 3.7 (Transportation Network 2-SuperHyperGraph of the I-90 Corridor). Let $G = (V, E, \tau, \ell, \kappa)$ be the I-90 segment graph and let

$$\mathcal{E} = \{\{u, v\} : (u, v) \in E\} \cup \{\{i\} \cup \{j\} : (i, j) \in E : |\cdot| \geq 2\} \cup \{\{i\} \cup \{j\} : (j, i) \in E : |\cdot| \geq 2\}$$

be its hyperedge family (as in Example 4.5). For $n = 2$, the Transportation Network 2-SuperHyperGraph is

$$V_2 = \mathcal{P}^2(V), \quad E_2 = \left\{ \mathcal{P}(e) \setminus \{\emptyset\} \mid e \in \mathcal{E} \right\},$$

with weight-functions

$$\tau^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \tau_H(e), \quad \ell^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \ell_H(e), \quad \kappa^{(2)}(\mathcal{P}(e) \setminus \{\emptyset\}) = \kappa_H(e).$$

We highlight two representative superedges:

(a) Binary link between Boston and Worcester:

For the hyperedge

$$e_{BW} = \{\text{Boston}, \text{Worcester}\},$$

its level-2 superedge is

$$\mathcal{P}(e_{BW}) \setminus \{\emptyset\} = \{\{\text{Boston}\}, \{\text{Worcester}\}, \{\text{Boston}, \text{Worcester}\}\}.$$

This inherits

$$\tau^{(2)}(\mathcal{P}(e_{BW}) \setminus \{\emptyset\}) = \tau_H(e_{BW}) = 1.25, \quad \ell^{(2)}(\cdot) = 113, \quad \kappa^{(2)}(\cdot) = 2000.$$

(b) Junction at Worcester:

For the junction hyperedge

$$e_W = \{\text{Boston}, \text{Worcester}, \text{Springfield}\},$$

its level-2 superedge is

$$\begin{aligned} \mathcal{P}(e_W) \setminus \{\emptyset\} = & \{\{\text{Boston}\}, \{\text{Worcester}\}, \{\text{Springfield}\}, \\ & \{\text{Boston}, \text{Worcester}\}, \{\text{Boston}, \text{Springfield}\}, \{\text{Worcester}, \text{Springfield}\}, \\ & \{\text{Boston}, \text{Worcester}, \text{Springfield}\}\}. \end{aligned}$$

This superedge carries

$$\begin{aligned} \tau^{(2)}(\mathcal{P}(e_W) \setminus \{\emptyset\}) &= \tau_H(e_W) = \max\{1.25, 1.00\} = 1.25, \\ \ell^{(2)}(\cdot) &= \ell_H(e_W) = \max\{113, 88\} = 113, \quad \kappa^{(2)}(\cdot) = \kappa_H(e_W) = 2000 + 1800 = 3800. \end{aligned}$$

Example 3.8 (Transportation Network 2-SuperHyperGraph of the Amtrak Northeast Corridor). Let $G = (V, E, \tau, \ell, \kappa)$ model the Amtrak Northeast Corridor with

$$V = \{\text{Washington}, \text{Philadelphia}, \text{New York}, \text{Boston}, \text{Albany}\},$$

$$E = \{(\text{Washington}, \text{Philadelphia}), (\text{Philadelphia}, \text{New York}), (\text{New York}, \text{Boston}), (\text{New York}, \text{Albany})\}.$$

Typical parameters are

$$\tau(e) = \begin{cases} 1.5, & e = (\text{Washington}, \text{Philadelphia}), \\ 1.25, & e = (\text{Philadelphia}, \text{New York}), \\ 4.00, & e = (\text{New York}, \text{Boston}), \\ 2.50, & e = (\text{New York}, \text{Albany}), \end{cases}$$

$$\ell(e) = \begin{cases} 225, & e = (\text{Washington}, \text{Philadelphia}), \\ 150, & e = (\text{Philadelphia}, \text{New York}), \\ 338, & e = (\text{New York}, \text{Boston}), \\ 260, & e = (\text{New York}, \text{Albany}), \end{cases}$$

$$\kappa(e) = \begin{cases} 20, & e = (\text{Washington}, \text{Philadelphia}), \\ 25, & e = (\text{Philadelphia}, \text{New York}), \\ 15, & e = (\text{New York}, \text{Boston}), \\ 10, & e = (\text{New York}, \text{Albany}). \end{cases}$$

The hyperedge set for G is

$$\mathcal{E} = \{ \{ \text{Washington}, \text{Philadelphia} \}, \{ \text{Philadelphia}, \text{New York} \}, \\ \{ \text{New York}, \text{Boston} \}, \{ \text{New York}, \text{Albany} \}, \{ \text{New York}, \text{Boston}, \text{Albany} \} \}.$$

For $n = 2$, the 2-SuperHyperGraph is

$$V_2 = \mathcal{P}^2(V),$$

$$E_2 = \{ \mathcal{P}(e) \setminus \{ \emptyset \} \mid e \in \mathcal{E} \},$$

with weight-functions propagated by

$$\tau^{(2)}(\mathcal{P}(e) \setminus \{ \emptyset \}) = \tau_H(e),$$

$$\ell^{(2)}(\mathcal{P}(e) \setminus \{ \emptyset \}) = \ell_H(e),$$

$$\kappa^{(2)}(\mathcal{P}(e) \setminus \{ \emptyset \}) = \kappa_H(e).$$

Two illustrative superedges are:

- For $e_{phNY} = \{ \text{Philadelphia}, \text{New York} \}$,

$$\mathcal{P}(e_{phNY}) \setminus \{ \emptyset \} = \{ \{ \text{Philadelphia} \}, \{ \text{New York} \}, \{ \text{Philadelphia}, \text{New York} \} \},$$

carrying $\tau^{(2)} = 1.25$, $\ell^{(2)} = 150$, $\kappa^{(2)} = 25$.

- For the junction $e_{NY} = \{ \text{New York}, \text{Boston}, \text{Albany} \}$,

$$\mathcal{P}(e_{NY}) \setminus \{ \emptyset \} = \{ \{ \text{New York} \}, \{ \text{Boston} \}, \{ \text{Albany} \}, \dots, \{ \text{New York}, \text{Boston}, \text{Albany} \} \},$$

carrying $\tau^{(2)} = \max\{4.00, 2.50\} = 4.00$, $\ell^{(2)} = \max\{338, 260\} = 338$, $\kappa^{(2)} = 15 + 10 = 25$.

Theorem 3.9. For each integer $n \geq 1$, $\text{TNHG}^{(n)}$ is an n -SuperHyperGraph, and it generalizes the Transportation Network HyperGraph in the sense that

$$\text{TNHG}^{(1)} \cong (V, \mathcal{E}, \tau_H, \ell_H, \kappa_H).$$

Proof. (i) n -SuperHyperGraph structure: By construction,

$$V_n = \mathcal{P}^n(V) \quad \text{and} \quad E_n \subseteq \mathcal{P}(V_n) \setminus \{ \emptyset \}.$$

Thus $\text{TNHG}^{(n)} = (V_n, E_n, \tau^{(n)}, \ell^{(n)}, \kappa^{(n)})$ satisfies the definition of an n -SuperHyperGraph.

(ii) Generalization of the HyperGraph: When $n = 1$, note that $\mathcal{P}^0(e) = e$ for each $e \in \mathcal{E}$. Hence

$$V_1 = \mathcal{P}^1(V) = \mathcal{P}(V), \quad E_1 = \{ \mathcal{P}^0(e) \mid e \in \mathcal{E} \} = \mathcal{E},$$

and $\tau^{(1)}(e) = \tau_H(e)$, $\ell^{(1)}(e) = \ell_H(e)$, $\kappa^{(1)}(e) = \kappa_H(e)$. There is a natural bijection $\iota : V \rightarrow \{ \{v\} : v \in V \} \subseteq V_1$, identifying each original node with its singleton. Under this identification, the level-1 superhypergraph $\text{TNHG}^{(1)} = (V_1, E_1, \tau^{(1)}, \ell^{(1)}, \kappa^{(1)})$ is isomorphic to the Transportation Network HyperGraph $(V, \mathcal{E}, \tau_H, \ell_H, \kappa_H)$.

Therefore, for all $n \geq 1$, the sequence of structures $\text{TNHG}^{(n)}$ forms a hierarchy of valid n -SuperHyperGraphs that at $n = 1$ recover and thus generalize the level-1 Transportation Network HyperGraph. $\square$

4. Conclusion and Future Work

In this work, we have generalized traditional river and transportation network graphs into the hypergraph and superhypergraph realms by defining two novel structures—River Network HyperGraph and Transportation Network HyperGraph—and their hierarchical extensions, the River Network SuperHyperGraph and Transportation Network SuperHyperGraph.

Looking ahead, we plan to enrich these models by incorporating uncertainty frameworks such as Fuzzy Sets [43–45], Intuitionistic Fuzzy Sets [46, 47], HyperFuzzy Sets [48–50], Vague sets [51, 52], Hesitant Fuzzy Sets [53, 54], Picture Fuzzy Sets [55–58], Neutrosophic Sets [59, 60], and Plithogenic Sets [61, 62]. We also hope that further progress will be made in computational experiments and algorithmic investigations.

Funding

This work was carried out without external financial support.

Acknowledgments

We are grateful to all colleagues and reviewers whose feedback and expertise improved this manuscript. We also thank the authors of the cited literature for establishing the foundations upon which this study builds, and our institutions for providing the resources that enabled this research.

Data Availability

No data were generated or analyzed in the course of this theoretical investigation. We encourage future empirical studies to test and extend the ideas presented here.

Ethical Approval

Not applicable.

Conflicts of Interest

The authors declare that they have no conflicts of interest.

Disclaimer

The concepts introduced in this paper are theoretical and have not yet been validated empirically. Readers should independently verify all references and may encounter inadvertent errors. The views expressed here are solely those of the authors and do not necessarily reflect the positions of their affiliated organizations.

References

- [1] Reinhard Diestel. Graduate texts in mathematics: Graph theory.
- [2] MS Sunitha and Sunil Mathew. Fuzzy graph theory: a survey. *Annals of Pure and Applied mathematics*, 4(1):92–110, 2013.
- [3] Jonathan L Gross, Jay Yellen, and Mark Anderson. *Graph theory and its applications*. Chapman and Hall/CRC, 2018.
- [4] Claude Berge. *Hypergraphs: combinatorics of finite sets*, volume 45. Elsevier, 1984.
- [5] Alain Bretto. Introduction to hypergraph theory and its use in engineering and image processing. *Advances in Imaging and Electron Physics*, 131:1–64, 2004. URL <https://api.semanticscholar.org/CorpusID:115532388>.
- [6] Alain Bretto. Hypergraph theory. *An introduction. Mathematical Engineering*. Cham: Springer, 1, 2013.
- [7] Yifan Feng, Haoxuan You, Zizhao Zhang, Rongrong Ji, and Yue Gao. Hypergraph neural networks. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pages 3558–3565, 2019.
- [8] Yuxin Wang, Quan Gan, Xipeng Qiu, Xuanjing Huang, and David Wipf. From hypergraph energy functions to hypergraph neural networks. In *International Conference on Machine Learning*, pages 35605–35623. PMLR, 2023.
- [9] Luotao Liu, Feng Huang, Xuan Liu, Zhankun Xiong, Menglu Li, Congzhi Song, and Wen Zhang. Multi-view contrastive learning hypergraph neural network for drug-microbe-disease association prediction. In *International Joint Conference on Artificial Intelligence*, 2023. URL <https://api.semanticscholar.org/CorpusID:260845944>.
- [10] Wei Li, Bin Xiang, Fan Yang, Yuchen Rong, Yanbin Yin, Jianhua Yao, and Han Zhang. scmhn: a novel hypergraph neural network for integrative analysis of single-cell epigenomic, transcriptomic and proteomic data. *Briefings in bioinformatics*, 24 6, 2023. URL <https://api.semanticscholar.org/CorpusID:265031925>.
- [11] Shuai Wang, Jiayi Shen, Athanasios Efthymiou, Stevan Rudinac, Monika Kackovic, Nachoem Wijnberg, and Marcel Worring. Prototype-enhanced hypergraph learning for heterogeneous information networks. In *International Conference on Multimedia Modeling*, pages 462–476. Springer, 2024.
- [12] Takaaki Fujita and Florentin Smarandache. A concise study of some superhypergraph classes. *Neutrosophic Sets and Systems*, 77: 548–593, 2024. URL <https://fs.unm.edu/nss8/index.php/111/article/view/5416>.
- [13] Mohammad Hamidi, Florentin Smarandache, and Elham Davneshvar. Spectrum of superhypergraphs via flows. *Journal of Mathematics*, 2022(1):9158912, 2022.
- [14] Shouxian Zhu. Neutrosophic n-superhypernetwork: A new approach for evaluating short video communication effectiveness in media convergence. *Neutrosophic Sets and Systems*, 85:1004–1017, 2025.

- [15] N. B. Nalawade, M. S. Bapat, S. G. Jakkewad, G. A. Dhanorkar, and D. J. Bhosale. Structural properties of zero-divisor hypergraph and superhypergraph over $\mathbb{Z}_n$: Girth and helly property. *Panamerican Mathematical Journal*, 35(4S):485, 2025. ISSN 1064-9735.
- [16] Mohammad Hamidi, Florentin Smarandache, and Mohadeseh Taghinezhad. *Decision Making Based on Valued Fuzzy Superhypergraphs*. Infinite Study, 2023.
- [17] Florentin Smarandache. *Extension of HyperGraph to n-SuperHyperGraph and to Plithogenic n-SuperHyperGraph, and Extension of HyperAlgebra to n-ary (Classical-/Neutro-/Anti-) HyperAlgebra*. Infinite Study, 2020.
- [18] Mohammed Alqahtani. Intuitionistic fuzzy quasi-supergraph integration for social network decision making. *International Journal of Analysis and Applications*, 23:137–137, 2025.
- [19] Florentin Smarandache. *SuperHyperFunction, SuperHyperStructure, Neutrosophic SuperHyperFunction and Neutrosophic SuperHyperStructure: Current understanding and future directions*. Infinite Study, 2023.
- [20] Ajoy Kanti Das, Rajat Das, Suman Das, Bijoy Krishna Debnath, Carlos Granados, Bimal Shil, and Rakhal Das. A comprehensive study of neutrosophic superhyper bci-semigroups and their algebraic significance. *Transactions on Fuzzy Sets and Systems*, 8(2):80, 2025.
- [21] Florentin Smarandache. Superhyperstructure & neutrosophic superhyperstructure, 2024. URL <https://fs.unm.edu/SHS/>. Accessed: 2024-12-01.
- [22] Takaaki Fujita. Review of probabilistic hypergraph and probabilistic superhypergraph. *Spectrum of Operational Research*, 3(1): 319–338, 2025.
- [23] Florentin Smarandache. *Introduction to the n-SuperHyperGraph-the most general form of graph today*. Infinite Study, 2022.
- [24] Judy L Meyer, David L Strayer, J Bruce Wallace, Sue L Eggert, Gene S Helfman, and Norman E Leonard. The contribution of headwater streams to biodiversity in river networks 1. *JAWRA Journal of the American Water Resources Association*, 43(1):86–103, 2007.
- [25] James H Thorp, Martin C Thoms, and Michael D Delong. The riverine ecosystem synthesis: biocomplexity in river networks across space and time. *River Research and Applications*, 22(2):123–147, 2006.
- [26] Ryan A Sponseller, James B Heffernan, and Stuart G Fisher. On the multiple ecological roles of water in river networks. *Ecosphere*, 4(2):1–14, 2013.
- [27] Dachuan Shi, Jiyun Song, Qilong Zhong, Soe W Myint, Peng Zeng, and Yue Che. Cooling wisdom of ‘water towns’: How urban river networks can shape city climate? *Remote Sensing of Environment*, 300:113925, 2024.
- [28] Nikolas Kirschstein and Yixuan Sun. The merit of river network topology for neural flood forecasting. *arXiv preprint arXiv:2405.19836*, 2024.
- [29] Yuqin Gao, Xuan Xiao, Mingming Ding, Yuqiang Tang, and Hongyu Chen. Evaluation of plain river network hydrologic connectivity based on improved graph theory. In *IOP Conference Series: Earth and Environmental Science*, volume 178, page 012002. IOP Publishing, 2018.
- [30] Yuping Han, Yao Xu, Runxiang Cao, and Zhongpei Liu. Optimization framework for eco-hydrological connectivity schemes based on graph theory and waterfront accessibility. *Journal of Hydrology: Regional Studies*, 56:101975, 2024.
- [31] William J Mitsch and John W Day Jr. Restoration of wetlands in the mississippi–ohio–missouri (mom) river basin: Experience and needed research. *Ecological Engineering*, 26(1):55–69, 2006.
- [32] Debra L Taylor, David W Bolgrien, Ted R Angradi, Mark S Pearson, and Brian H Hill. Habitat and hydrology condition indices for the upper mississippi, missouri, and ohio rivers. *Ecological Indicators*, 29:111–124, 2013.
- [33] RE Rathbun. Regression equations for disinfection by-products for the mississippi, ohio and missouri rivers. *Science of the Total Environment*, 191(3):235–244, 1996.
- [34] Yosef Sheffi. *Urban transportation networks*, volume 6. Prentice-Hall, Englewood Cliffs, NJ, 1985.
- [35] Roger Guimera, Stefano Mossa, Adrian Turttschi, and LA Nunes Amaral. The worldwide air transportation network: Anomalous centrality, community structure, and cities’ global roles. *Proceedings of the National Academy of Sciences*, 102(22):7794–7799, 2005.
- [36] César Ducruet and Igor Lugo. Structure and dynamics of transportation networks: models, methods and applications. *The SAGE handbook of transport studies*, pages 347–364, 2013.
- [37] Feng Xie and David Levinson. *Evolving transportation networks*. Springer Science & Business Media, 2011.
- [38] Faruk Serin and Süleyman Mete. Public transportation graph: A graph theoretical model of public transportation network for efficient trip planning. *Pamukkale Üniversitesi Mühendislik Bilimleri Dergisi*, 25(4):468–472, 2019.
- [39] Renata Żochowska and Piotr Soczówka. Analysis of selected transportation network structures based on graph measures. *Zeszyty Naukowe. Transport/Politechnika Śląska*, 2018.

- [40] Aleksandr Rakhmangulov and Pavel Mishkurov. Method and algorithm of spatial-temporal graph formation for dynamic transportation system. 2023.
- [41] Mohammed Alam and Edward Fekpe. Application of geographic information systems technology in freight data analysis: Case study of i-90/i-94 corridor analysis. *Transportation research record*, 1625(1):173–183, 1998.
- [42] David C Wilcock. High-speed ground transportation feasibility study: I-90 (massachusetts turnpike) corridor–boston, massachusetts, to the new york state line. *Transportation Research Record*, (1470), 1994.
- [43] Lotfi A Zadeh. Fuzzy sets. *Information and control*, 8(3):338–353, 1965.
- [44] TM Nishad, Talal Ali Al-Hawary, and B Mohamed Harif. General fuzzy graphs. *Ratio Mathematica*, 47, 2023.
- [45] Hongxing Li and Vincent C Yen. *Fuzzy sets and fuzzy decision-making*. CRC press, 1995.
- [46] Ajoy Kanti Das. On partially included intuitionistic fuzzy rough relations. *Afrika Matematika*, 27(5):993–1001, 2016.
- [47] Muhammad Akram, Bijan Davvaz, and Feng Feng. Intuitionistic fuzzy soft k-algebras. *Mathematics in Computer Science*, 7:353–365, 2013.
- [48] Young Bae Jun, Kul Hur, and Kyoung Ja Lee. Hyperfuzzy subalgebras of bck/bci-algebras. *Annals of Fuzzy Mathematics and Informatics*, 2017.
- [49] Takaaki Fujita and Florentin Smarandache. Examples of fuzzy sets, hyperfuzzy sets, and superhyperfuzzy sets in climate change and the proposal of several new concepts. *Climate Change Reports*, 2:1–18, 2025.
- [50] Jayanta Ghosh and Tapas Kumar Samanta. Hyperfuzzy sets and hyperfuzzy group. *Int. J. Adv. Sci. Technol*, 41:27–37, 2012.
- [51] W-L Gau and Daniel J Buehrer. Vague sets. *IEEE transactions on systems, man, and cybernetics*, 23(2):610–614, 1993.
- [52] Humberto Bustince and P Burillo. Vague sets are intuitionistic fuzzy sets. *Fuzzy sets and systems*, 79(3):403–405, 1996.
- [53] Vicenç Torra and Yasuo Narukawa. On hesitant fuzzy sets and decision. In *2009 IEEE international conference on fuzzy systems*, pages 1378–1382. IEEE, 2009.
- [54] Vicenç Torra. Hesitant fuzzy sets. *International journal of intelligent systems*, 25(6):529–539, 2010.
- [55] Bui Cong Cuong and Vladik Kreinovich. Picture fuzzy sets-a new concept for computational intelligence problems. In *2013 third world congress on information and communication technologies (WICT 2013)*, pages 1–6. IEEE, 2013.
- [56] Raed Hatamleh, Abdullah Al-Husban, Sulima Ahmed Mohammed Zubair, Mawahib Elamin, Maha Mohammed Saeed, Eisa Abdolmaleki, Takaaki Fujita, Giorgio Nardo, and Arif Mehmood Khattak. Ai-assisted wearable devices for promoting human health and strength using complex interval-valued picture fuzzy soft relations. *European Journal of Pure and Applied Mathematics*, 18(1): 5523–5523, 2025.
- [57] Sankar Das, Ganesh Ghorai, and Madhumangal Pal. Picture fuzzy tolerance graphs with application. *Complex & Intelligent Systems*, 8 (1):541–554, 2022.
- [58] Ajay Devaraj et al. Picture fuzzy labelling graphs with an application. *Annals of Optimization Theory and Practice*, 3(3):117–134, 2020.
- [59] Said Broumi, Mohamed Talea, Assia Bakali, and Florentin Smarandache. Single valued neutrosophic graphs. *Journal of New theory*, (10):86–101, 2016.
- [60] Ajoy Kanti Das, Nandini Gupta, Carlos Granados, Rakhil Das, and Suman Das. Neutrosophic approach to water quality assessment: A case study of gomati river, the largest river in tripura, india. *Neutrosophic Systems with Applications*, 22:1–12, 2024.
- [61] Nivetha Martin. Plithogenic swara-topsis decision making on food processing methods with different normalization techniques. *Advances in Decision Making*, 69, 2022.
- [62] P Sathya, Nivetha Martin, and Florentine Smarandache. Plithogenic forest hypersoft sets in plithogenic contradiction based multi-criteria decision making. *Neutrosophic Sets and Systems*, 73:668–693, 2024.